

Ssa 455 Ocr Sm 10 2013

Understanding the Ssa 455 Ocr Sm 10 2013: A Comprehensive Guide

In the world of industrial equipment and precision engineering, part numbers like **Ssa 455 Ocr Sm 10 2013** can often seem cryptic to the uninitiated. However, for engineers, procurement specialists, and maintenance professionals, understanding the structure and significance of such a code is essential for ensuring correct specification, proper installation, and long-term operational reliability. This article provides a thorough exploration of the Ssa 455 Ocr Sm 10 2013, breaking down its likely meaning, typical applications, key features, and best practices for maintenance and integration within larger systems. Whether you are sourcing a replacement component or seeking to understand a specification sheet, this guide offers valuable insights into this specific model identifier.

What Does Ssa 455 Ocr Sm 10 2013 Mean?

Industrial part numbers are rarely random strings of characters. Instead, they are carefully constructed codes that convey critical information about the component. While the exact meaning can vary by manufacturer, the structure of **Ssa 455 Ocr Sm 10 2013** suggests a product that belongs to a specific series or family. Let us break down a plausible interpretation of this code, keeping in mind that understanding the logic behind such coding helps in cross-referencing and identifying compatible parts.

- **SSA:** This prefix likely denotes a product series or family. It could stand for "Stainless Steel Actuator," "Standard Service Assembly," or a specific model line from a particular manufacturer. Recognizing the SSA prefix helps narrow down the category of equipment, often pointing toward fluid handling, pneumatic, or

hydraulic applications.

- **455:** This numerical segment frequently indicates a physical dimension, such as a bore size, stroke length, or pressure rating. In many actuator and cylinder models, numbers like 455 correspond to a specific diameter in millimeters or a force rating in Newtons. It is a primary identifier for performance capacity.
- **OCR:** This is often an acronym for a specific feature or configuration. "OCR" could represent "Over-Center Return," "Oil Cooled Return," or "O-Ring Compression Retainer." Alternatively, it might indicate a material specification, such as "Oil and Chemical Resistant." The exact meaning depends on the manufacturer's internal coding system.
- **SM:** This common abbreviation in industrial contexts typically stands for "Service Manual," "Specification Model," or "Seal Material." If the part number includes a reference to a manual or specific material composition, it underscores the importance of using the correct configuration for safety and performance.
- **10 2013:** This trailing segment almost certainly represents a date code. In the format MM YYYY, "10 2013" translates to October 2013. This indicates the design revision, manufacturing date, or the date of the applicable specification standard. Recognizing a date code is crucial for understanding which generation of the product you are dealing with and whether updates have

been made since its release.

By understanding these components, professionals can better appreciate that the **Ssa 455 Ocr Sm 10 2013** is not just a random label but a detailed descriptor of a specific piece of industrial equipment designed for particular operating conditions.

Primary Applications and Use Cases

Components identified by codes like **Ssa 455 Ocr Sm 10 2013** are typically found in demanding industrial environments. Based on the decoded elements, this component is most likely a pneumatic or hydraulic cylinder, or an actuator assembly. Its robust designation suggests it is built for precision, durability, and consistent performance under load.

Manufacturing and Automation

In automated production lines, precision actuators are the muscles that power movement. The Ssa 455 Ocr Sm 10 2013 is ideally suited for tasks such as clamping, pushing, lifting, and positioning in assembly stations. Its likely stainless steel construction (SSA) makes it resistant to corrosion and suitable for environments where hygiene or exposure to washdown chemicals is a concern, such as in food processing or pharmaceutical packaging.

Material handling equipment relies on rugged and repeatable motion. The Ssa 455 Ocr Sm 10 2013 can be integrated into conveyor diverters, palletizers, and automated storage and retrieval systems. The date code (10 2013) suggests a mature design that has been proven in the field, offering reliability that is essential for minimizing costly downtime in logistics operations.

Process Control and Valve Actuation

In industries like oil and gas, chemical processing, and water treatment, precise control over valves is critical. The Ssa 455 Ocr Sm 10 2013 may serve as a linear or rotary actuator for controlling gate valves, ball valves, or butterfly valves. The "OCR" feature could indicate a fail-safe return mechanism, ensuring the valve returns to a safe position in the event of a power or pressure loss, which is a vital safety consideration.

Key Features and Performance Benefits

When evaluating a component like the Ssa 455 Ocr Sm 10 2013, it is important to focus on the tangible benefits it brings to an operation. Its design characteristics likely contribute to several performance advantages that make it a preferred choice for engineers.

The materials and construction methods implied by the model code suggest a high level of durability. Equipment from this class is typically designed to withstand millions of cycles without significant wear. The use of corrosion-resistant materials and high-quality seals reduces the frequency of replacement, leading to a lower total cost of ownership over the equipment's lifespan.

Operational Precision and Repeatability

Precision is non-negotiable in modern automated systems. The Ssa 455 Ocr Sm 10 2013 is built to operate with tight tolerances, ensuring that every cycle is identical to the last. This repeatability is essential for maintaining product quality and process stability in high-speed manufacturing environments.

Adaptability and Integration

A well-designed industrial component must be easy to integrate into existing systems. The Ssa 455 Ocr Sm 10 2013 likely features standard mounting interfaces and port sizes, allowing for straightforward replacement of older units or seamless inclusion into new designs. Its compatibility with common control systems and power sources further simplifies installation and reduces engineering overhead.

Safety and Reliability

The inclusion of a specific seal material and a potential over-center return mechanism indicates a strong focus on safety. In critical applications, the failure of an actuator can have severe consequences. The robust design of the Ssa 455 Ocr Sm 10 2013 minimizes the risk of sudden failure, and its predictable performance allows for effective preventive maintenance scheduling.

Installation and Setup Considerations

Proper installation is critical to achieving the expected performance from any industrial component. Working with a part like the **Ssa 455 Ocr Sm 10 2013** requires attention to detail from the moment it arrives on site. Following these guidelines will help ensure a smooth setup process and prevent early-life failures.

1. **Verify Compatibility:** Before beginning installation, double-check that the specifications of the Ssa 455 Ocr Sm 10 2013 match the requirements of your system. Confirm physical dimensions, port sizes, stroke length, and pressure ratings against the original equipment specifications.
2. **Inspect for Shipping Damage:** Carefully examine the unit for any signs of impact, corrosion, or seal damage that may have occurred

during transit. Even minor damage can lead to premature wear or leakage.

3. **Clean All Connections:** Ensure that hydraulic or pneumatic lines are clean and free of debris before connecting. Contaminants are a leading cause of seal failure and internal component wear.
4. **Follow Torque Specifications:** Use a torque wrench to tighten all mounting bolts and fittings to the manufacturer's recommended values. Over-tightening can distort the housing, while under-tightening can lead to leaks and instability.
5. **Purge Air from the System:** If the unit is part of a hydraulic circuit, carefully purge any air from the system before applying full pressure. Air trapped in the system can cause erratic movement and damage internal seals.
6. **Perform a Functional Test:** After installation, run the unit through several slow cycles at low pressure to verify smooth operation and check for any unusual noises or leaks before bringing the system to full operating parameters.

Maintenance Best Practices for Long-Term Reliability

To maximize the service life of the **Ssa 455 Ocr Sm 10 2013**, a proactive maintenance program is essential. The original design from October 2013 reflects the engineering standards of that period, but modern maintenance techniques can further extend its

will help identify potential issues before they cause costly downtime.

Regular Inspection Schedule

Establish a routine for visual and operational inspections. Check for external leaks around seals and fittings. Listen for unusual sounds such as hissing, knocking, or squealing, which can indicate internal wear or contamination. Inspect the mounting hardware and alignment regularly, as vibration can cause fasteners to loosen over time.

Fluid and Lubrication Management

The condition of the operating fluid is directly linked to the health of the actuator. For hydraulic units, regularly sample and test the fluid for contamination and degradation. Replace filters according to the manufacturer's schedule. For pneumatic units, ensure that the air supply is clean, dry, and properly lubricated if required by the system design.

Seal and Component Replacement

Seals are typically the first components to wear out. Keep a spare seal kit for the Ssa 455 Ocr Sm 10 2013 on hand to minimize downtime when replacement becomes necessary. When replacing seals, carefully inspect the cylinder bore and piston rods for scoring or

Documentation and Record Keeping

Maintain a log of all maintenance activities performed on the unit. Record the date of installation, dates of inspections, and any parts replaced. This historical data is invaluable for predicting future maintenance needs and for making informed decisions about when to replace the unit entirely.

Troubleshooting Common Issues

Even with the best maintenance practices, issues can arise. Understanding the most common problems associated with equipment like the **Ssa 455 Ocr Sm 10 2013** allows technicians to diagnose and resolve them quickly, minimizing operational disruptions.

Erratic or Slow Movement

If the actuator moves inconsistently or slower than expected, the most common causes are insufficient pressure or flow, air in the system (for hydraulic units), or internal seal leakage. Check the power supply and control signals first, then proceed to check for internal bypass.

External Leakage

Le